

Product Information Sheet



FyreWrap® DPS Insulation Dryer Protection System

INTRODUCTION

Unifrax's FyreWrap® DPS Insulation is a high-temperature insulation blanket specifically designed, UL tested and certified to provide a single layer, one-hour rated flexible enclosure around dryer, residential kitchen, and bathroom exhaust ductwork.

DRYER EXHAUST APPLICATIONS

FyreWrap DPS is an innovative product that provides a safe and cost-effective means to achieve a one-hour fire resistance rated zero clearance enclosure for routing dryer ductwork, from start to finish, through rated wood truss/joist construction as prescribed by the International Building and Mechanical Codes.

FyreWrap DPS Insulation offers the following product features:

- Lightweight, flexible product form
- Scrim encapsulated
- Easy to cut, fabricate, wrap around ducts, pipes or cables
- Thin, single-layer design
- High-temperature, low biopersistance fiber

PRODUCT COMPONENTS

Core Material: FyreWrap DPS Insulation incorporates Insulfrax® Thermal Insulation as its core material. Insulfrax is a high-temperature insulation made from a calcia, magnesia, silica chemistry designed to enhance biosolubility. It provides excellent insulation in a noncombustible blanket product form.

TYPICAL SYSTEM PROPERTIES

ISO 6944
 UL 1479 (ASTM E814), CAN/ULC S115
 Intertek Laboratories Listed
 ASTM E136 Noncombustibility Test
 ASTM E84, UL 723, ULC-S102

UL Assembly Nos. V-32 & V-38, ULC Assembly No. FRD-29
 UL Assembly Nos. F-C-7057, F-C-7058
 Applied Fire Protection, File 16341-3
 Passes
 UL File No. R14514
 Unfaced Blanket

Flame Spread Rating:
 S moke Developed Rating:

Zero < 25
 Zero < 50



FyreWrap® DPS Insulation – Dryer Protection System

Encapsulating Material: The core insulation blanket is completely encapsulated in an aluminum foil, fiberglass reinforced scrim covering. This scrim provides additional handling strength as well as protection from moisture absorption and tearing.

TYPICAL PRODUCT PROPERTIES

Thickness	½"
Density	8pcf
Covering	Scrim Encapsulated
Product Availability	16" w x 25LF 24" w x 25LF 26" w x 25LF 48" w x 25LF



Data are average results of tests conducted under standard procedures and are subject to variation. Results should not be used for specification purposes.

For minimum order quantities, material lead time and availability, please contact our Customer Service Department. *Nonstandard thickness, basis weight, widths, lengths and facings (or unfaced E-Mat) are available upon request

FyreWrap® DPS Insulation Dryer Protection System

INSTALLATION


FyreWrap DPS Insulation consists of a single-layer system applied directly on to the surface of the duct or combustible item.

DRYER APPLICATIONS

Install the insulation around the duct to provide a tightly compressed butt joint or 1" overlap on all material seams. The 16" width DPS product facilitates linear installation around 4" diameter dryer ductwork without material cutting or scrap. The same technique can be used with wrapping 26" wide FyreWrap DPS on 7" diameter dryer ductwork. To temporarily secure the insulation, optional use of foil tape is permitted. Seal all cut edges and seams with aluminum foil tape to ensure there is no exposed fiber. 18 gauge steel tie wire should be utilized for permanent attachment.

Locate the wire 1/2" from the blanket edge and on maximum 12" centers. Twist tension the wire to firmly hold the wrap system in place, but not so tight as to cut or damage the blanket. Seal all cut edges and seams with aluminum foil tape. Installation details are provided below for additional illustration.

Alkegen has a wide range of FyreWrap fire protection materials available to provide passive fire protection solutions in a variety of applications in the commercial building, industrial facility and transportation industries. For additional information about product performance or for assistance identifying the recommended product for your fire protection application, please contact Alkegen at 716-768-6500 and ask for Fire Protection Application Engineering.



The following is a registered trademark of Alkegen: FyreWrap, Insulfrax.
The test data shown are average results of tests conducted under standard procedures and are subject to variation. Results should not be used for specification purposes. Product Information Sheets are periodically updated by Alkegen. Before relying on any data or other information in this Product Information Sheet, you should confirm that it is still current and has not been superseded. A Product Information Sheet that has been superseded may contain incorrect, obsolete and/or irrelevant data and other information.

Alkegen
 Headquarters
 5215 N. O'Connor Blvd, Suite 2300
 Irving, TX 75039
 Telephone: 716-768-6500
 Website: www.alkegen.com
 Email: info@alkegen.com