HT MOULDABLE 175

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 09/01/2023 Revision date: 09/01/2023 Version: 1.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : HT MOULDABLE 175
UFI : SK5A-F0PP-K00C-TVM1

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : For industrial use within high temperature applications.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier
Alkegen (formerly Unifrax)
Mill Lane, Rainford
UK– WA11 8LP St Helens, Merseyside
United Kingdom
T + 44 (0) 1744 88 7600 - F + 44 (0) 1744 88 9916

Email competent person
reachsds@alkegen.com

Distributor
Alkegen (formerly Unifrax)
Kleinreinsdorf 62
DE– 07989 Teichwolframsdorf
Germany
T + 49 (0) 366 24 40020 - F + 49 (0) 366 24 40099

Distributor
Alkegen (formerly Unifrax)
17 Rue Antoine Durafour
42420 Lorette
France
T +33 (0) 477 737 032 - F +33 (0) 477 733 991

Distributor
Alkegen (formerly Unifrax)
Shaftsbury Street
DE23 8XA Derby
United Kingdom
T +44 (0) 1332 331808

Distributor
Alkegen (formerly Unifrax)
Ruská 311, Pozorka
CZ– 417 03 Dubí 3
Czech Republic
T + 42 (0) 417 800 356 - F + 42 (0) 417 539 838

Distributor
Alkegen (formerly Unifrax)
Via Volonterio 19
21047 Saronno (VA)
Italy
T +39 02 967 01 808 - F +39 02 962 5721

Distributor
Alkegen (formerly Unifrax)
Cristobal Bordiu 20
ES– 28003 Madrid
Spain
T + 34 91 395 2279 - F + 34 91 395 2124

1.4. Emergency telephone number

Emergency number : Occupational Hygiene and CARE: Tel: + 44 (0) 1744 887603; Email: reachsds@alkegen.com; (8.15-17.10 h); Language : English

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07

Signal word (CLP) : Warning

Contains : 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

Precautionary statements (CLP) : P261 - Avoid breathing mist, vapours, spray.
P280 - Wear protective gloves, eye protection, face protection.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

PBT: not relevant – no registration required
vPvB: not relevant – no registration required
Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
aluminium oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanediol (107-21-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methyl-2H-isothiazol-3-one (2682-20-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
aluminium oxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 1344-28-1 EC-No.: 215-691-6 REACH-no: 01-2119529248-35-xxxx	≥ 25 – < 50	Not classified
Polycrystalline wools (PCW) substance with national workplace exposure limit(s) (GB)	CAS-No.: 675106-31-7 REACH-no: 01-2119456884-25-0003	≥ 10 – < 20	Not classified
ethanediol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	≥ 2.5 – < 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373

1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=670 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	< 0.1	Acute Tox. 2 (Inhalation), H330 (ATE=0.1 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=242 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=120 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 EUH071

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits**
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60-xxxx	(0.05 ≤C < 100) Skin Sens. 1, H317
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50-xxxx	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Complete protective clothing.

Other information : Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container closed when not in use. Keep cool. Protect against frost.

Storage temperature : 10 – 25 °C

Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethanediol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	52 mg/m³
IOEL TWA [ppm]	20 ppm
IOEL STEL	104 mg/m³
IOEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m³ particulate 52 mg/m³ vapour
WEL TWA (OEL TWA) [2]	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m³ vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

aluminium oxide (1344-28-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA) [1]	4 mg/m³ respirable dust 10 mg/m³ inhalable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Polycrystalline wools (PCW) (675106-31-7)	
United Kingdom - Occupational Exposure Limits	
Local name	MMMF (Machine-made mineral fibre)
WEL TWA (OEL TWA) [1]	5 mg/m³ (except for refractory ceramic fibres and special purpose fibres)
WEL TWA (OEL TWA) [2]	2 fibers/ml (except for refractory ceramic fibres and special purpose fibres)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

ethanediol (107-21-1)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	106 mg/kg bodyweight/day
Long-term - local effects, inhalation	35 mg/m³

DNEL/DMEL (General population)	
Long-term - systemic effects, dermal	53 mg/kg bodyweight/day
Long-term - local effects, inhalation	7 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC aqua (intermittent, freshwater)	10 mg/l
PNEC aqua (intermittent, marine water)	10 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	37 mg/kg dwt
PNEC sediment (marine water)	3.7 mg/kg dwt
PNEC (Soil)	
PNEC soil	1.53 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	199.5 mg/l

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6.81 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1.2 mg/m³
Long-term - systemic effects, dermal	0.345 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4.03 µg/L
PNEC aqua (marine water)	0.403 µg/L
PNEC aqua (intermittent, freshwater)	1.1 µg/L
PNEC aqua (intermittent, marine water)	0.11 µg/L
PNEC (Sediment)	
PNEC sediment (freshwater)	49.9 µg/kg dw
PNEC sediment (marine water)	4.99 µg/kg dw
PNEC (Soil)	
PNEC soil	3 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1.03 mg/l

2-methyl-2H-isothiazol-3-one (2682-20-4)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.043 mg/m³
Long-term - local effects, inhalation	0.021 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.053 mg/kg bodyweight/day

Acute - local effects, inhalation	0.043 mg/m³
Long-term - systemic effects,oral	0.027 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.021 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	3.39 µg/L
PNEC aqua (marine water)	3.39 µg/L
PNEC aqua (intermittent, freshwater)	3.39 µg/L
PNEC aqua (intermittent, marine water)	3.39 µg/L
PNEC (Soil)	
PNEC soil	0.047 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.23 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing. EN ISO 13688. EN 13034

Hand protection:
Chemically resistant protective gloves. Nitrile rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Particle filter. P2. EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

Other information:
Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	white to slightly yellow. Beige.
Appearance	:	Paste.

Odour	:	odourless.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive properties	:	Product is not explosive.
Oxidising properties	:	Non oxidizing.
Explosive limits	:	Not available
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	Not available
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	9 – 10
pH solution concentration	:	100 %
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	:	Not classified (Based on available data, the classification criteria are not met)

HT MOULDABLE 175	
ATE CLP (oral)	> 10000 mg/kg bodyweight

ethanediol (107-21-1)	
LD50 oral	≈ 1600 mg/kg bodyweight (human (estimated value))
ATE CLP (oral)	500 mg/kg bodyweight

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: 9 – 10

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: 9 – 10

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

ethanediol (107-21-1)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day (OECD 452 method)
NOAEL (dermal, rat/rabbit, 90 days)	2200 – 4400 mg/kg bodyweight/day (OECD 410 method)
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information

Other information : Chronic effects:
Lifetime rat inhalation studies of polycrystalline fiber show that at the maximum dose level tested, there was no evidence of lung cancer, lung fibrosis or any other significant adverse effect. Intraperitoneal, intratracheal and intrapleural studies in rats, together with two in vitro tests, have all shown negative results. Despite some study limitations, it is important to note the consistent lack of carcinogenic response in animal studies.

In 1988, the International Agency for Research on Cancer (IARC) considered the carcinogenicity of several groups of fibers. One grouping they considered was a poorly defined collection of disparate fiber types [polycrystalline fiber, refractory ceramic fiber (referred to as RCF) and single crystal whiskers] into a broad, single category they termed “ceramic fibers”. The IARC monograph clearly indicated that test data specific to polycrystalline fibers were negative, but according to the IARC classification principles, positive results with other fiber types led to the conclusion that all fibers in the group should be considered as possible human carcinogens (IARC Category 2B). In a subsequent monograph on MMVF (2002), IARC did not specifically re-evaluate polycrystalline fiber. The Annual Report on Carcinogens prepared by the National Toxicology Program (NTP), (latest edition) classified “ceramic fibers (respirable size)” as reasonably anticipated to be carcinogens.

As produced most polycrystalline fibers, including Saffil, have fiber diameters too large to be respirable. Numerous scientific studies suggest that the potential toxicity of a respirable fiber is directly related to bio-persistence (the length of time it take for the fiber to clear the lung). Based on limited in-vitro laboratory analysis, which measure the dissolution rate of fibers in simulated lung fluid, polycrystalline fibers are known to be relatively durable.
Data from respiratory surveillance studies are not available for PCW workers. In a small cohort of workers exposed to PCW with historical co-exposures to RCF and other fibers, there was no evidence of interstitial lung disease on chest x-rays nor an accelerated rate of loss of lung function on pulmonary function testing. Symptom responses could not be attributed to or excluded from exposure to PCW as a consequence of the prior fiber exposures,Irritant Properties
When tested using approved methods (Directive 67/548/EC, Annex V, Method B4), fibres contained in this material give negative results. Man made mineral fibres, can produce a mild irritation resulting in itching or rarely, in some sensitive individuals, in slight reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by a temporary mechanical effect.

Other Animal Studies
These materials have been designed to allow rapid clearance from lung tissue. And this low biopersistence has been confirmed in many studies on AES using EU protocol ECB/TM/27(rev 7).
When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect. In lifetime chronic studies there was no exposure-related effect more than would be seen with any “inert” dust.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Not rapidly degradable

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	2.18 mg/l (96 h; Onchorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	2.94 mg/l (48 h; Daphnia magna; OECD 202)
ErC50 algae	0.15 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)

NOEC chronic algae	0.055 mg/l (72 h; Pseudokirchneriella subcapitata; OECD 201)

2-methyl-2H-isothiazol-3-one (2682-20-4)	
LC50 - Fish [1]	4.77 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))
EC50 - Crustacea [1]	0.934 mg/l (48 h; Daphnia magna; (OECD 202 method))
EC50 72h algae	0.103 mg/l (72 h, Pseudokirchneriella Subcapita; (OECD 201 method))
ErC50 algae	0.072 mg/l (OECD 201 method)
NOEC chronic fish	4.93 mg/l (98 d; Oncorynchus mykiss; (OECD 210 method))
NOEC chronic crustacea	0.044 mg/l (21 d; Daphnia magna; (OECD 211 method))
NOEC chronic algae	0.05 mg/l (5 d; Pseudokirchneriella subcapitata; (OECD 201 method))

12.2. Persistence and degradability

ethanediol (107-21-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 – 100 % (10 d; (OECD 301A method))

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	85 % (63 d; (OECD 301C method))

2-methyl-2H-isothiazol-3-one (2682-20-4)	
Persistence and degradability	Not readily biodegradable. (OECD 301B method). (OECD 301D method).

aluminium oxide (1344-28-1)	
Persistence and degradability	Not applicable.

Polycrystalline wools (PCW) (675106-31-7)	
Persistence and degradability	Not applicable.

12.3. Bioaccumulative potential

ethanediol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.36 (Quantitative structure-activity relationship (QSAR))
Bioaccumulative potential	Bioaccumulation unlikely.

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
BCF - Fish [1]	6.95 (OECD 305 method)
Partition coefficient n-octanol/water (Log Kow)	0.7 (20 °C; pH 7; Test method EU A.8)

2-methyl-2H-isothiazol-3-one (2682-20-4)	
Partition coefficient n-octanol/water (Log Pow)	-0.486 (25 °C; (OECD 107 method))
Bioaccumulative potential	Bioaccumulation unlikely.

aluminium oxide (1344-28-1)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Bioaccumulative potential	Not applicable.

Polycrystalline wools (PCW) (675106-31-7)	
Bioaccumulative potential	Not applicable.

12.4. Mobility in soil

ethanediol (107-21-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (Quantitative structure-activity relationship (QSAR))

2-methyl-2H-isothiazol-3-one (2682-20-4)	
Surface tension	68.8 mN/m (19 °C, EEC Method A5)
Ecology - soil	Low mobility (soil).

Polycrystalline wools (PCW) (675106-31-7)	
Ecology - soil	Not applicable.

12.5. Results of PBT and vPvB assessment

HT MOULDABLE 175
PBT: not relevant – no registration required
vPvB: not relevant – no registration required

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.

Product/Packaging disposal recommendations : Recycle or dispose of in compliance with current legislation.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport
Not applicable

Transport by sea
Not applicable

Air transport
Not applicable

Inland waterway transport
Not applicable

Rail transport
Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Take note of Directive 94/33/EC on the protection of young people at work.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(b)	HT MOULDABLE 175 ; ethanediol

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Data sources : European Chemicals Agency, http://echa.europa.eu/.

Other information : Occupational Hygiene: dawn.webster@alkegen.com.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Sens. 1	H317	Calculation method

KFT SDS EU 06

The information presented on this SDS (1) provides details on material identity, manufacturer/supplier information, hazard characterization and prevention, emergency response and other specialized information, (2) is considered to be accurate to the best of our knowledge, information and good faith belief as of the date of publication, (3) is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release of the material named, (4) should be read and used in conjunction with the company's relevant literature, (5) relates only to the specific material designated and may not be valid for such material used in combination with any other material or process and (6) is provided without warranty, expressed or implied, in law or in fact, of merchantability or fitness for a particular purpose. This document does not constitute a product specification and should not be relied on as such. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product.